

Crystal Cut® 155 *Synthetic Coolant Concentrate*

FEATURES

- Excellent Corrosion Control
- Excellent for Cast Iron
- Hydrocarbon Free
- Long Lasting and Bio-Resistant
- Low Foam
- Translucent

GENERAL DESCRIPTION

Crystal Cut 155 is the best in class full synthetic metal working fluid. Crystal Cut 155 provides excellent tool life with ceramic, diamond and carbide tools. You can rely on machine cleanliness and corrosion protection without compromising operator Health and Safety. Crystal Cut 155 has extended sump life and avoids cast iron related problems such as chip clinking.

APPLICATIONS

Primary		Secondary	
Grinding	Sawing	Centerless Grinding	Diamond Tip Turning
Milling	Tube Mill Manufacturing	Cutting	Turning

MATERIALS

Primary		Secondary	
Armor Plate	Powdered Metals	Aluminum	Composites
Cast Iron	Steel	Carbon	Graphite

INSTRUCTIONS

Always premix coolant before adding to the machine sump. When mixing coolant by hand it is important to always add the concentrate to the water and then agitate. For best results, a Hangsterfer's recommended proportioning unit should be used. To maintain recommended concentration, make-up should be added at one-fourth the desired concentration. Always check concentration with a Refractometer. To maintain 6%: first charge the machine at 6%, then, as needed, add make-up as much as 1.5%. Avoid adding straight water or concentrate directly to machine.

OPERATION	CONCENTRATION		
	%	Ratio Concentrate: Water	Refractometer
General Machining	7 - 10	1:14 – 1:10	1.4 - 2.0
General Grinding	4 - 6	1:25 – 1:16	0.8 - 1.2

MAINTENANCE

Crystal Cut 155 is a bio-resistant synthetic designed to control the growth of bacteria and fungus. Regular maintenance is required for maximum performance. Concentration should be monitored regularly with a calibrated refractometer. The refractometer reading needs to be multiplied by 5.0 in order to determine the actual concentration (e.g. 2 on the Refractometer = 10%). Tramp oils should be removed from the coolant surface regularly to help reduce bacterial growth. Keep the coolant system free of cleaners, solvents, and other contaminants.

PRODUCT CHARACTERISTICS

Product Name: Crystal Cut 155		Concentration Dilution Table		
Form	Liquid	%	<i>Ratio</i> Concentrate: Water	Refractometer
Color	Colorless	10%	1:10	2.0
Odor	Mild	9%	1:11	1.8
Specific Gravity	1.03	8%	1:12.5	1.6
Viscosity: SUS @ 100°F	6.8	7%	1:14	1.4
cSt @ 40°C	1.5	6%	1:16.5	1.2
Flash Point, COC, °F/°C	Non-Flammable	5%	1:20	1.0
Fire Point, COC, °F/°C	Non-Flammable	4%	1:25	0.8
Solubility in Water	Soluble	3%	1:33	0.6
pH @ 10%	9.3	2%	1:50	0.4
Chlorine	None	1%	1:100	0.2

Refractive Index Multiplier = 5

WASTE TREATMENT

Dispose of in accordance with local, state, federal and international laws. If and when it is necessary to dispose of waste fluids, the amount of waste can be greatly reduced by separating the water from the oil and contaminants which accumulate through normal machining. You can often reduce your waste disposal by more than 80% through conventional methods such as Ultra-Filtration, Chemical Treatment or Evaporation. After approval by your local, state, or federal authorities, the waste water may be sent to the sewer or discharged into waters, and the separated oils may be removed for recycling, sale or disposal.

SHIPPING UNITS

All Hangsterfer's products are available in pails, drums and Intermediate Bulk Containers (Totes). This product is REACH compliant and is distributed worldwide.

Date: 8/21/15 Rev: 11/18/15

Disclaimer: All reasonable care has been taken to ensure that the information contained in this publication is true and accurate. No warranty is expressed or implied regarding the accuracy of the data. The general description, recommended uses, application data and statements in the product literature are guidelines. Because this product may be used for a variety of applications over which Hangsterfer's Laboratories, Inc. has no control, Hangsterfer's Laboratories, Inc. assumes no liability for incidental, consequential, or direct damages of any kind, regardless of causes, including negligence. Also, seller is not liable for any loss, damage or liability resulting from the use of the product in the buyer's manufacturing processes or in combination with other substances. MSDS's are available for all Hangsterfer's products and should be consulted as needed.

