

## Safety Data Sheet 123 Ultra EP Multi-Service Grease

### **SDS Revision Date: 09/16/2021**

#### 1. Identification

1.1. Product identifier

**Product Identity** 123 Ultra EP Multi-Service Grease

Alternate Names 123

1.2. Relevant identified uses of the substance or mixture and uses advised against

**Intended use** See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name Southwestern Petroleum Lubricants LLC

3401 Quorum Drive, Suite 360 Fort Worth, Texas 76137

**Emergency** 

**24 hour Emergency Telephone No.** 734 930-0009

Customer Service: Southwestern Petroleum Emergency numbers call Chemtrec 24/7 USA and

**Lubricants LLC** Canada 1-800-424-9300 or 1-703-527-3887

## 2. Hazard(s) identification

#### 2.1. Classification of the substance or mixture

Carc. 1B;H350 May cause cancer.

#### 2.2. Label elements



H350 May cause cancer.

#### [Prevention]:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P281 Use personal protective equipment as required.

#### [Response]:

P308+313 IF exposed or concerned: Get medical advice or attention.

#### [Storage]:

P405 Store locked up.

#### [Disposal]:

P501 Dispose of contents or container in accordance with local and national regulations.

## 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Distillates (petroleum), hydrotreated light naphthenic CAS Number: 0064742-53-6	10 - 25	Asp. Tox. 1;H304	
Distillate (petroleum) hydrotreated heavy naphthenic CAS Number: 0064742-52-5	10 - 25	Asp. Tox. 1;H304	
Calcium carbonate CAS Number: 0000471-34-1	5 - 10	Not Classified	

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret

#### Section 4. First aid measures

### 4.1. Description of first aid measures

**General** In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

**Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or

stopped, give artificial respiration. If unconscious, place in the recovery position and

obtain immediate medical attention. Give nothing by mouth.

**Eyes** Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart

and seek medical attention.

**Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a

recognized skin cleanser.

**Ingestion** DO NOT INDUCE VOMITING! If swallowed, vomiting may occur spontaneously.

If vomiting occurs, keep head below hips to prevent aspiration into lungs. Rinse

mouth thoroughly. Get medical attention.

## 4.2. Most important symptoms and effects, both acute and delayed

#### **Overview**

If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. The onset of respiratory symptoms may be delayed for several hours after exposure. Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhea. Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 3 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.

Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the

<sup>\*</sup>PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16

eyes may cause irritation and soreness with possible reversible damage. Check section 2.2 (GHS Label Elements) for further details.

## Section 5. Fire-fighting measures

#### 5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO<sub>2</sub>, powder, water spray.

Unsuitable extinguishing media: Do not use; water jet.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

## 5.3. Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

ERG Guide No. ----

#### Section 6. Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

### 6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

### 6.3. Methods and material for containment and cleaning up

Slippery when spilled. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

Local authorities should be advised if significant spillages cannot be contained.

## Section 7. Handling and storage

#### 7.1. Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

Avoid prolonged or repeated contact with skin. Avoid inhaling vapor and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closeable containers.

This material has the potential to be a static accumulator. Proper grounding and bonding procedures should be used during all bulk transfer operations.

Use product with caution around heat, sparks, pilot lights, static electricity and open flame.

Check section 2.2 (GHS Label Elements) for further details. - [Prevention]:

### 7.2. Conditions for safe storage, including any incompatibilities

Storage Temperature: -50 - 50C ( -58 - 122F)

For containers or container linings, use mild steel or high density polyethylene.

Do not use PVC.

Incompatible materials: Strong oxidizing agents and acids.

Check section 2.2 (GHS Label Elements) for further details. - [Storage]:

## 7.3. Specific end use(s)

No available information

## Section 8. Exposure controls / personal protection

## 8.1. Control parameters

## Exposure

CAS No.	Ingredient	Source	Value
0000471-34-1	Calcium carbonate	OSHA	TWA 10 mg/m3 (total) TWA 5 mg/m3 (resp)
		ACGIH	No Established Limit
		NIOSH	TWA 10 mg/m3 (total) TWA 5 mg/m3 (resp)
0064742-52-5	Distillate (petroleum) hydrotreated heavy naphthenic		No Established Limit
			No Established Limit
		NIOSH	No Established Limit
0064742-53-6 Distillates (petroleum), hydrotreated light		OSHA	No Established Limit
	naphthenic	ACGIH	No Established Limit
		NIOSH	No Established Limit

Contains mineral oil. The exposure limits for oil mist are 5 mg/m3 OSHA PEL and 10 mg/m3 ACGIH.

## 8.2. Exposure controls

**Respiratory** If workers are exposed to concentrations above the exposure limit they must use the

appropriate, certified respirators.

Eyes Protective safety glasses recommended

**Skin** Skin protection is not required under normal conditions of use. Oil impervious

gloves and oil impermeable apron recommended.

**Engineering Controls** Provide adequate ventilation. Where reasonably practicable this should be achieved

by the use of local exhaust ventilation and good general extraction. If these are not

sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices Use good personal hygiene practices. Wash hands before eating, drinking, smoking

or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Check section 2.2 (GHS Label Elements) for further details. - [Prevention]:

#### Section 9. Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Physical State Lubricating Grease

Color Thick Blue Odor None to Mild.

**Odor threshold**No available information

pH 8.0 Melting point / freezing point 300C

Initial boiling point and boiling range

No available information

Flash Point

F°C, Test method: (Open

**Evaporation rate (Ether = 1)** Nil

Flammability (solid, gas)

Upper/lower flammability or explosive limits

No available information

Lower Explosive Limit: 1.0

**Upper Explosive Limit:** 9.0

Vapor pressure (Pa)No available informationVapor DensityNo available information

Relative Density 0.92

**Solubility in Water Partition coefficient n-octanol/water (Log Kow)**Not miscible in water.

No available information

Auto-ignition temperature 330C

Decomposition temperatureNo available informationViscosity (cSt)No available information

VOC Content 000

9.2. Other information

DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)

## Section 10. Stability and reactivity

#### 10.1. Reactivity

Hazardous Polymerization will not occur.

## 10.2. Chemical stability

Stable under normal circumstances.

## 10.3. Possibility of hazardous reactions

No available information

### 10.4. Conditions to avoid

Excessive heat and open flame.

# 10.5. Incompatible materials

Strong oxidizing agents and acids.

## 10.6. Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

### **Section 11. Toxicological information**

#### **Acute toxicity**

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50,	Skin LD50,	Inhalation	Inhalation	Inhalation
------------	------------	------------	------------	------------	------------

	mg/kg	mg/kg	Vapor LC50, mg/L/4hr	Dust/Mist LC50, mg/L/4hr	Gas LC50, ppm
Distillates (petroleum), hydrotreated light naphthenic - (64742-53-6)	> 5,000.00, Rat - Category: NA	> 5,000.00, Rabbit - Category: NA	No data available	No data available	No data available
Distillate (petroleum) hydrotreated heavy naphthenic - (64742-52-5)	> 5,000.00, Rat - Category: NA	No data available	No data available	5.70, Rat - Category: NA	No data available
Calcium carbonate - (471-34-1)	>2,000.00, Rat - Category: 5	>2,000.00, Rat - Category: 5	No data available	No data available	No data available

Carcinogen Data

CAS No.	Ingredient	Source	Value		
0000471-34-1 Calcium carbonate		OSHA	Regulated Carcinogen: No		
		NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
		ACGIH			
0064742-52-5	Distillate (petroleum) hydrotreated	OSHA	Regulated Carcinogen: No		
	heavy naphthenic	NTP			
		IARC			
0064742-52-6	D: ('11 4 ( 4 1 ) 1 1 4 4 1	ACGIH	No Established Limit		
0064742-53-6	Distillates (petroleum), hydrotreated light naphthenic	OSHA NTP	Regulated Carcinogen: No		
	ingin imprime	IARC	Known: No; Suspected: No Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
		ACGIH	No Established Limit		
Classification	_				
Classification		Category	-		
Acute toxicity (oral)			Not Applicable		
Acute toxicity (dermal)			Not Applicable		
Acute toxicity (inhalation)			Not Applicable		
Skin corrosion/irritation			Not Applicable		
Serious eye d	amage/irritation		Not Applicable		
Respiratory so	ensitization		Not Applicable		
Skin sensitiza	tion		Not Applicable		
Germ cell mutagenicity			Not Applicable		
Carcinogenicity		1B	May cause cancer.		
Reproductive toxicity			Not Applicable		
STOT-single	exposure		Not Applicable		
STOT-repeate	ed exposure		Not Applicable		
Aspiration ha	zard		Not Applicable		

# Section 12. Ecological information

# 12.1. Toxicity

Poorly soluble mixture. May cause physical fouling of aquatic organisms. Expected to be harmful: LL/EL/IL50 10-100 mg/l (to aquatic organisms) LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract.

# **Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Distillates (petroleum), hydrotreated light naphthenic - (64742-53-6)	Not Available	Not Available	Not Available
Distillate (petroleum) hydrotreated heavy naphthenic - (64742-52-5)	5,000.00, Oncorhynchus mykiss	1,000.00, Daphnia magna	1,000.00 (96 hr), Scenedesmus subspicatus
Calcium carbonate - (471-34-1)			

101.00, Oncorhynchus mykiss	101.00, Daphnia magna	Not Available
IIIykiss		

## 12.2. Persistence and degradability

Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.

### 12.3. Bioaccumulative potential

Contains components with the potential to bioaccumulate.

## 12.4. Mobility in soil

Liquid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile. Floats on water.

#### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

#### 12.6. Other adverse effects

No available information

## Section 13. Disposal considerations

#### 13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

### **Section 14. Transport information**

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Regulated	Not Regulated	Not Regulated
14.2. UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
14.3. Transport	<b>DOT Hazard Class:</b> Not	<b>IMDG:</b> Not Applicable	Air Class: Not Applicable
hazard class(es)	Applicable <b>Sub Class:</b> Not Applicable	Sub Class: Not Applicable	Sub Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental	hazards		
IMDC	M ' D 11 / A NI		

**IMDG** Marine Pollutant: No;

14.6. Special precautions for user

No available information

## **Section 15. Regulatory information**

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected

regulations are represented.

**Toxic Substance** All components of this material are either listed or exempt from listing on the TSCA

Control Act (TSCA) Inventory.

US EPA Tier II Hazards

Fire: No
Sudden Release of Pressure: No

Reactive: No Immediate (Acute): No Delayed (Chronic): Yes

### **EPCRA 302 Extremely Hazardous:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

## **EPCRA 313 Toxic Chemicals:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### **Proposition 65 - Carcinogens (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

## **Proposition 65 - Developmental Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

## **Proposition 65 - Female Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

## **Proposition 65 - Male Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

## **Proposition 65 Label Warning:**

This product contains no chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

#### Section 16. Other information

#### **SDS Revision Date** 09/16/2021

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H304 May be fatal if swallowed and enters airways.

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders

End of Document