1. Identification				
1.1. Product identifier				
Product Identity	165 MolyXP Universal Extreme Pressure Grease			
Alternate Names	165			
1.2. Relevant identified uses of the substance or mixture and uses advised against				
Intended use	See Technical Data Sheet.			
1.3. Details of the supplier of the safety data sheet	t			
Company Name	Southwestern Petroleum Lubricants LLC			
	3401 Quorum Drive, Suite 360			
	Fort Worth, Texas 76137			
Emergency				
24 hour Emergency Telephone No.	734 930-0009			
Customer Service: Southwestern Petroleum Lubricants LLC	Emergency numbers call Chemtrec 24/7 USA and Canada 1-800-424-9300 or 1-703-527-3887			

2. Hazard(s) identification

2.1. Classification of the substance or mixture

2.2. Label elements

H315 Causes skin irritation.

H350 May cause cancer.

[Prevention]:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P264 Wash thoroughly after handling.

P280 Wear protective gloves, eye protection, face protection.

[Response]:

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P308+313 IF exposed or concerned: Get medical advice or attention.

P321 Specific treatment (see information on this label).

P332+313 IF SKIN IRRITATION OCCURS: Get medical advice or attention.

P362 Take off contaminated clothing and wash before reuse.

[Storage]:

P405 Store locked up.

[Disposal]:

P501 Dispose of contents or container in accordance with local and national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Distillate (petroleum) hydrotreated heavy naphthenic CAS Number: 0064742-52-5	50 - 75	Asp. Tox. 1;H304	
Distillates (petroleum), hydrotreated light naphthenic CAS Number: 0064742-53-6	25 - 50	Asp. Tox. 1;H304	
Polybutene CAS Number: 0009003-29-6	10 - 25	Asp. Tox. 1;H304 Skin Irrit. 2;H315	
Graphite CAS Number: 0007782-42-5	1 - 5	Not Classified	

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret. *PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

4.1. Description of first aid measures

Se and measures
In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.
Remove to fresh air, keep patient warm and at rest. If breathing is irregular or
stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
DO NOT INDUCE VOMITING! If swallowed, vomiting may occur spontaneously. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Rinse mouth thoroughly. Get medical attention.
symptoms and effects, both acute and delayed
If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. The onset of respiratory symptoms may be delayed for several hours after exposure. Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhea. Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 3 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure. Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the

eyes may cause irritation and soreness with possible reversible damage. Check section 2.2 (GHS Label Elements) for further details.

Section 5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.

Unsuitable extinguishing media: Do not use; water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

5.3. Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

ERG Guide No. ----

Section 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

6.3. Methods and material for containment and cleaning up

Slippery when spilled. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly. Local authorities should be advised if significant spillages cannot be contained.

Section 7. Handling and storage

7.1. Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

Avoid prolonged or repeated contact with skin. Avoid inhaling vapor and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closeable containers.

This material has the potential to be a static accumulator. Proper grounding and bonding procedures should be used during all bulk transfer operations.

Use product with caution around heat, sparks, pilot lights, static electricity and open flame.

Check section 2.2 (GHS Label Elements) for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Storage Temperature: -50 - 50C (-58 - 122F)
For containers or container linings, use mild steel or high density polyethylene.
Do not use PVC.
Incompatible materials: Strong oxidizing agents and acids.
Check section 2.2 (GHS Label Elements) for further details. - [Storage]:
7.3. Specific end use(s)
No available information

Section 8. Exposure controls / personal protection

_

8.1. Control parameters

Exposure				
CAS No.	Ingredient	Source	Value	
0007782-42-5	Graphite	OSHA	TWA 15 mg/m3 TWA 15 mppcf	
		ACGIH	TWA: 2 mg/m3	
		NIOSH	TWA 2.5 mg/m3 (resp)	
0009003-29-6	Polybutene	OSHA	No Established Limit	
		ACGIH	No Established Limit	
		NIOSH	No Established Limit	
0064742-52-5 Distillate (petroleum) hydrotreated heavy		OSHA	No Established Limit	
1	naphthenic	ACGIH	No Established Limit	
		NIOSH	No Established Limit	
	Distillates (petroleum), hydrotreated light naphthenic	OSHA	No Established Limit	
		ACGIH	No Established Limit	
		NIOSH	No Established Limit	

Contains mineral oil. The exposure limits for oil mist are 5 mg/m3 OSHA PEL and 10 mg/m3 ACGIH.

8.2. Exposure controls

Respiratory	If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
Eyes	Protective safety glasses recommended
Skin	Skin protection is not required under normal conditions of use. Oil impervious gloves and oil impermeable apron recommended.
Engineering Controls	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.
Check section 2.2 (GHS	S Label Elements) for further details - [Prevention].

Section 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

1 0	1 1		
Physical State	Lubricating Grease		
Color	Semi Solid Black, viscous gel		
Odor	None		
Odor threshold	No available information		
рН	7.8		
Melting point / freezing point	315 C		

Initial boiling point and boiling range	No available information
Flash Point	°F °C, Test method: (Open/Close cup)
Evaporation rate (Ether = 1)	Nil
Flammability (solid, gas)	No available information
Upper/lower flammability or explosive limits	Lower Explosive Limit: 0.9
	Upper Explosive Limit: 7.0
Vapor pressure (Pa)	No available information
Vapor Density	>5
Relative Density	0.95
Solubility in Water	Not miscible in water.
Partition coefficient n-octanol/water (Log Kow)	No available information
Auto-ignition temperature	330 C
Decomposition temperature	No available information
Viscosity (cSt)	No available information
VOC Content	0.0001
9.2. Other information	

DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)

Section 10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability
Stable under normal circumstances.
10.3. Possibility of hazardous reactions
No available information
10.4. Conditions to avoid
Excessive heat and open flame.
10.5. Incompatible materials
Strong oxidizing agents and acids.
10.6. Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Distillate (petroleum) hydrotreated heavy naphthenic - (64742- 52-5)	> 5,000.00, Rat - Category: NA	No data available	No data available	5.70, Rat - Category: NA	No data available
Distillates (petroleum), hydrotreated light naphthenic - (64742- 53-6)	> 5,000.00, Rat - Category: NA	 > 5,000.00, Rabbit - Category: NA 	No data available	No data available	No data available
Polybutene - (9003-29-6)	> 10,000, Rat - Category: NA	No data available	No data available	No data available	No data available
Graphite - (7782-42-5)	> 2,000.00, Rat - Category: 4	No data available	No data available	> 2,000.00, Rat - Category: NA	No data available

Carcinogen Data

CAS No.	Ingredient	Source	Value		
0007782-42-5	Graphite	OSHA	Regulated Carcinogen: No		
		NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
		ACGIH	No Established Limit		
0009003-29-6	Polybutene	OSHA	Regulated Carcinogen: No		
		NTP IARC	Known: No; Suspected: No Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
		ACGIH	No Established Limit		
0064742-52-5	Distillate (petroleum) hydrotreated	OSHA	Regulated Carcinogen: No		
0001712 32 3	heavy naphthenic	NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
		ACGIH	No Established Limit		
0064742-53-6	Distillates (petroleum), hydrotreated	OSHA	Regulated Carcinogen: No		
	light naphthenic	NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
		ACGIH	No Established Limit		
Classification	n	Category	Hazard Description		
Acute toxicity	(oral)		Not Applicable		
Acute toxicity	(dermal)		Not Applicable		
Acute toxicity	y (inhalation)		Not Applicable		
Skin corrosio	n/irritation		Not Applicable		
Serious eye d	amage/irritation		Not Applicable		
Respiratory se	ensitization		Not Applicable		
Skin sensitiza	tion		Not Applicable		
Germ cell mu	tagenicity		Not Applicable		
Carcinogenicity			Not Applicable		
Reproductive	toxicity		Not Applicable		
STOT-single			Not Applicable		
STOT-repeate	ed exposure		Not Applicable		
Aspiration ha	zard		Not Applicable		

Section 12. Ecological information

12.1. Toxicity

Poorly soluble mixture. May cause physical fouling of aquatic organisms. Expected to be harmful: LL/EL/IL50 10-100 mg/l (to aquatic organisms) LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Distillate (petroleum) hydrotreated heavy naphthenic - (64742-52-5)	5,000.00, Oncorhynchus mykiss	1,000.00, Daphnia magna	1,000.00 (96 hr), Scenedesmus subspicatus
Distillates (petroleum), hydrotreated light naphthenic - (64742-53-6)	Not Available	Not Available	Not Available
Polybutene - (9003-29-6)	> 10,000, Leuciscus idus	101.00, Daphnia magna	101.00 (72 hr), Pseudokirchneriella subcapitata
Graphite - (7782-42-5)	100.00, Danio rerio	> 100.00, Daphnia magna	> 100.00 (72 hr), Pseudokirchnerella subcapitata

12.2. Persistence and degradability

Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.

12.3. Bioaccumulative potential

Contains components with the potential to bioaccumulate.

12.4. Mobility in soil

Liquid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile. Floats on water.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No available information

Section 13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

Section 14. Transport information					
	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA		
14.1. UN number	Not Regulated	Not Regulated	Not Regulated		
14.2. UN proper shipping name	Not Regulated	Not Regulated	Not Regulated		
14.3. Transport hazard class(es)	DOT Hazard Class: Not Applicable Sub Class: Not Applicable	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable Sub Class: Not Applicable		
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable		
14.5. Environmental hazards					
IMDG	Marine Pollutant: No;				

14.6. Special precautions for user

No available information

Section 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Toxic SubstanceAll components of this material are either listed or exempt from listing on the TSCAControl Act (TSCA)Inventory.US EPA Tier II HazardsFire: No

Fire: No Sudden Release of Pressure: No Reactive: No Immediate (Acute): Yes Delayed (Chronic): Yes

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute. **EPCRA 313 Toxic Chemicals:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute. **Proposition 65 - Carcinogens (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute. **Proposition 65 - Developmental Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute. **Proposition 65 - Female Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute. **Proposition 65 Label Warning:**

This product contains no chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

SDS Revision Date 09/20/2021

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders

End of Document