

203 MolyXP Gear Lube

SDS Revision Date: 09/10/2021

1. Identification

Product identifier

Product Identity 203 MolyXP Gear Lube

Other means of identification 203

Relevant identified uses of the substance or mixture and uses advised against

See Technical Data Sheet.

Details of the supplier of the safety data sheet

Company Name: Southwestern Petroleum Lubricants LLC

3401 Quorum Drive Suite 360 Fort Worth, Texas 76137

Emergency:

1.4. Emergency telephone number: 734-930-0009

Emergency: numbers call Chemtrec 24/7 USA and

Canada 1-800-424-9300 or 1-703-527-3887

Customer Service: 800-359-5823

2. Hazard(s) identification

Classification of the substance or mixture

Skin Irrit. 3;H316 Causes mild skin irritation. (This category was not adopted by Canada)

Carc. 1B;H350 May cause cancer.

Label elements



Danger

H316 Causes mild skin irritation.

H350 May cause cancer.

[Prevention]:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves, eye protection, face protection.

[Response]:

P308+313 IF exposed or concerned: Get medical advice or attention.

P332+313 IF SKIN IRRITATION OCCURS: Get medical advice or attention.

[Storage]:

P405 Store locked up.

[Disposal]:

P501 Dispose of contents or container in accordance with local and national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the Hazardous Products Regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Distillate (petroleum) hydrotreated heavy naphthenic CAS Number: 0064742-52-5 Synonyms: Distillate (petroleum) hydrotreated heavy naphthenic, Distillates (petroleum), hydrotreated heavy naphthenic; baseoil-unspecified, Polymer binders and adhesive, Petroleum distillates, hydrotreated heavy naphthenic	60 - 100	Asp. Tox. 1;H304	
Distillates (petroleum), hydrotreated heavy paraffinic CAS Number: 0064742-54-7 Synonyms: Distillates (petroleum), hydrotreated heavy paraffinic,	7 - 13	Carc. 1B;H350	

Distillates (petroleum), hydrotreated heavy paraffinic; baseoil-unspecified, Petroleum distillates, hydrotreated heavy paraffinic			
Polybutene CAS Number: 0009003-29-6 Synonyms: Polybutene	7 - 13	Asp. Tox. 1;H304 Skin Irrit. 2;H315	

The actual concentration or concentration range is withheld as a trade secret.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular

or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the

eyelids apart and seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and

water or use a recognized skin cleanser.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT

induce vomiting.

Most important symptoms and effects, both acute and delayed

Overview Possible cancer hazard. Contains an ingredient which may cause cancer

based on animal data (See Section 3 and Section 15 for each ingredient).

Risk of cancer depends on duration and level of exposure.

Treat symptomatically. Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of

consciousness.

^{*}PBT/vPvB - PBT-substance or vPvB-substance.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Skin

Causes mild skin irritation. (This category was not adopted by Canada)

Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.

Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

See section 2 for further details. - [Prevention]:

Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong oxidizing agents and acids.

See section 2 for further details. - [Storage]:

Specific end use(s)

No available information

Section 8. Exposure controls / personal protection

Control parameters

Exposure

CAS No.	Ingredient	Source	Value
	09003- Polybutene	ACGIH	No Established Limit
29-6		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit

0064742-	Distillate (petroleum)	ACGIH	No Established Limit
52-5	hydrotreated heavy naphthenic	Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
	Yukon	No Established Limit	
	Distillates (petroleum), hydrotreated heavy paraffinic	ACGIH	No Established Limit
54-7		Alberta	No Established Limit
	pararrine	British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit

Prince Edwar Island	d No Established Limit
Quebec	No Established Limit
Saskatchewar	No Established Limit
Yukon	No Established Limit

Contains mineral oil. The exposure limits for oil mist are 5 mg/m3 OSHA PEL and 10 mg/m3 ACGIH.

Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they

must use the appropriate, certified respirators.

Eyes Protective safety glasses recommended

Skin Avoid skin contact. Protective gloves recommended.

Engineering Provide adequate ventilation. Where reasonably practicable this should be

Controls achieved by the use of local exhaust ventilation and good general

extraction. If these are not sufficient to maintain concentrations of

particulates and any vapour below occupational exposure limits suitable

respiratory protection must be worn.

Other Work Use good personal hygiene practices. Wash hands before eating, drinking,

Practices smoking or using toilet. Promptly remove soiled clothing and wash

thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

Appearance Black Viscous Liquid

Odour Characteristic of Petroleum.

Odour threshold No available information

PH No available information

Melting point / freezing point No available information

Initial boiling point and boiling range No available information

Flash Point °F °C, Test method: (Open/Close cup)

Evapouration rate (Ether = 1)

Flammability (solid, gas)

Upper/lower flammability or explosive limits

No available information

Lower Explosive Limit: 0.9

Unner Evalorive Limit: 7.0

Upper Explosive Limit: 7.0

Vapour pressure (Pa) No available information

Vapour Density >5
Relative Density 0.9

Solubility in Water No available information

Partition coefficient n-octanol/water (Log

Kow)

None

Auto-ignition temperature 260

Decomposition temperature No available information Viscosity (cSt) No available information

Other information

DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)

Section 10. Stability and reactivity

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.

Possibility of hazardous reactions

No available information

Conditions to avoid

Excessive heat and open flame.

Incompatible materials

Strong oxidizing agents and acids.

Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous

system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg		Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Distillate (petroleum) hydrotreated heavy naphthenic - (64742- 52-5)	> 5,000.00, Rat - Category: NA	No data available	No data available	5.70, Rat - Category: NA	No data available
Distillates (petroleum), hydrotreated heavy paraffinic - (64742-54- 7)	> 5,000.00, Rat - Category: NA	> 5,000.00, Rabbit - Category: NA	No data available	No data available	No data available
Polybutene - (9003-29-6)	> 10,000, Rat - Category: NA	No data available	No data available	No data available	No data available

Carcinogen Data

CAS No.	Ingredient	Source	Value
0009003- 29-6	Polybutene		Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0064742- 52-5	Distillate (petroleum) hydrotreated heavy		Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
	naphthenic	ACGIH	No Established Limit
0064742- 54-7	Distillates (petroleum),		Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit

hydrotreated heavy paraffinic			
Classification	Cate	egory	Hazard Description
Acute toxicity (oral)	_		Not Applicable
Acute toxicity (dermal)	_		Not Applicable
Acute toxicity (inhalation)	_		Not Applicable
Skin corrosion/irritation	3		Causes mild skin irritation. (This category was not adopted by Canada)
Serious eye damage/irritation	-		Not Applicable
Respiratory sensitization			Not Applicable
Skin sensitization			Not Applicable
Germ cell mutagenicity	_		Not Applicable
Carcinogenicity	1	В	May cause cancer.
Reproductive toxicity	_		Not Applicable
STOT-single exposure	_		Not Applicable
STOT-repeated exposure			Not Applicable
Aspiration hazard	-		Not Applicable

Possible routes of entry:

Symptoms and effects, both acute and delayed::

Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 3 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.

Treat symptomatically.

Skin

Causes mild skin irritation. (This category was not adopted by Canada)

Section 12. Ecological information

Toxicity

No additional information provided for this product. See Section 3 for chemical specific data. Aquatic Ecotoxicity

Ingredient 96 hr LC50 fish,	48 hr EC50 crustacea,	ErC50 algae,	
ingredient	mg/l	mg/l	mg/l

Distillate (petroleum) hydrotreated heavy naphthenic - (64742-52-5)	5,000.00, Oncorhynchus mykiss	1,000.00, Daphnia magna	1,000.00 (96 hr), Scenedesmus subspicatus
Distillates (petroleum), hydrotreated heavy paraffinic - (64742-54-7)	101.00, Pimephales promelas	> 10,000, Daphnia magna	100.00 (72 hr), Pseudokirchneriella subcapitata
Polybutene - (9003-29-6)	> 10,000, Leuciscus idus	101.00, Daphnia magna	101.00 (72 hr), Pseudokirchneriella subcapitata

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

No available information

Mobility in soil

No available information

Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

Other adverse effects

No available information

Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.

Section 14. Transport information

Classification Method: Classified as per Part 2, Sections 2.1 ? 2.8 of the Transportation of Dangerous Goods Regulations.

TDG (Domestic Surface IMO / IMDG (Ocean ICAO/IATA Transportation) Transportation)

UN number Not Regulated Not Regulated Not Regulated UN proper shipping Not Regulated Not Regulated Not Regulated

name

Transport hazard TDG Hazard Class: Not IMDG: Not Air Class: Not

class(es) Applicable Applicable Applicable

Sub Class: Not Applicable

Packing group Not Applicable Not Applicable Not Applicable

Environmental hazards

IMDG Marine Pollutant: No;

Special precautions for user

No available information

Section 15. Regulatory information

This product has been classified in accordance with the hazard criteria Hazardous Products Regulations (SOR/2015-17) and the SDS contains all of the information required by those regulations.

Canadian Domestic Substance List (DSL):

Distillate (petroleum) hydrotreated heavy naphthenic

Distillates (petroleum), hydrotreated heavy paraffinic

Lubricating oils, petroleum, hydrotreated spent

Molybdenum, N,N-bis(C11-14-branched and linear alkyl)carbamodithioate oxo thioxo complexes

Polybutene

Polyisobutylene

Canadian Non-Domestic Substance List (NDSL):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Section 16. Other information

SDS Revision Date 09/10/2021

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all

liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H350 May cause cancer.

End of Document